

Mini Waterproof Doorbell V30-1080P Outdoor Unit



	Description	No Memory Card or Battery, No Indoor Unit
	Features	Wireless Connection, Ultra-low Power Consumption, Remote Active Awakening, Quick Start
	Usage	Guests will be able to make video voice calls and take short videos. The owner will not need to open the door to know the information
	Wake up the way	The doorbell button awakens, PIR body detection wake up, Mobile Call
	Alarm Push	Push for 1 second
	Number of Users Online	Multiple users online simultaneously
	Dynamic DNS	Bring Your Own Dynamic Domain Name
	Processor	A powerful, high-performance, Programmable Media Realtek processor with built-in ARM926 @max. 440MHz and high-speed Video Co-processor
Collection	CCD	1/2.7 inch 1080p scan CMOS sensor
	Sensor Performance	Support Automatic White Balance, Automatic Gain Control, automatic backlighting compensation
	SNR	≥39dB
	Lens/ Visual Angle	2.6mm @F2.0/155°
	LED	Double filter automatic switching, Six 850-nm high power infrared lamp, night vision 10 meters
	IR Control	IR opens night vision, Automatic Detection of IR and ICR ; IR shuts the night vision function off the infrared and the ICR is fixed in daily viewing mode
Video	Compression	H.264 Main Profile/H.264 Baseline Profile/ MJPEG/JPEG Baseline, ADPCM/32kbps
	Video Coding	More stream: 1080P/15fps+720P/15fps+VGA/30fps+ QVGA/30fps+1080P@1fsJPEG snap
	Resolution	1080P
	Video Mode	Mobile detection video, doorbell button trigger video, Manual Video
Audio	Input	1 channel built-in - 48dB Microphone
	Output	Built-in speaker (8 Ω 1 w)
	Interphone	Two-way voice-speak, Bring Back the Echo Cancellation
Network	Network protocol	TCP/IP,HTTP,TCP,UDP,SMTP,FTP,DHCP,DNS, DDNS,NTP,UPnP,RTSP, P2P
	Wifi Mode	802.11b/g/n
	Wireless Security	WPS Security Encryption
	Wireless Connection	One-button WIFI Configuration
Other	Storage	The TF card stores the maximum support for 32gb
	Power	Battery Power Supply Two x 18650 Core International
	Power Consumption	Standby Current 200 uA/ Working Current 170mA
	Environment	- 10 ~ 50 °C, Humidity is < 95%
	Installation	Wall Mount
	Material	ABS
	Product Size	140mm x45.5mm x27.5mm
	Weight	90g/No battery